

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**  
 ERIN TOWNSHIP

For corners in

<u>MACOMB</u> <small>(County)</small>	Located In:	Corner Code #
1. Public Land Survey	T <u>1N.</u> R <u>13E</u>	<u>G-02</u>
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling	S _____ T _____ R _____	_____
in Section	S _____ T _____ R _____	_____
3. Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

205067  
 LIBER 9942 PAGE 532  
 12/26/2000 09:19:20 A.M.  
 MACOMB COUNTY, MI  
 CARMELLA SABAUGH, REG/DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4	●	3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	

I, JOHN R. FENN in a field survey on September 18, 2000 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Glo 1817 Wampler No evidence of original corner  
 1973 LCRC Robert L. Smith 16052 L.2459, P.585 Found PK nail No witnesses left  
 1979 LCRC Soderberg 17635 L.3218, P.53 Found 1/2" Rerod in monument Box  
 Plats 1941 Supervisor's Plat No. 6 of Sherman's Small Farms Subdivision L20, P44

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found a 1/2" rerod in a monument box on the centerline of Masonic Avenue (concrete) and the East Right of Way line of Little Mack Avenue. Several Irons to the South and West verified this location as the corner.  
 Distances: G-02 to G-01 G-02 to G-03  
 GLO 40 chains or 2640 feet GLO 40 chains or 2640 feet  
 Measure 2690.75 feet Measure 2688.96 feet

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I recommend that a standard 3/4" Iron Rod with a standard Macomb County Remonumentation Cap marked Act 345 23505 in an existing monument box be located at the determined position.

- S65°W 113.55" Set PK nail with Macomb County Remon tag in Southeast face Utility Pole
- N70°W 112.22' Centerline East Bolt on Metal Light Pole
- North 42.41' Southwest corner Brick Pillar
- S10°W 56.87' Set PK nail with Macomb County Remon tag in West face Utility Pole

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best position of the original corner.

Signed by John R. Fenn  
 Surveyor's Michigan License No. 23505



Date 12-19-2000

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER BOARD AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
11/21/00  
William E. Soderberg  
 WILLIAM E. SOLERBERG, P.S., CHAIRMAN

**G-02**

**ERIN TOWNSHIP**

**T.1N.,R.13E.**

**WEST QUARTER CORNER SECTION 3**

**EAST QUARTER CORNER SECTION 4**

**G-02 ERIN TOWNSHIP**

**RECORDED INFORMATION:**

**GLO: 1817 Wampler No evidence of original corner**

**LCRC'S**

**1973 Robert L. Smith L2459, P585 Found PK nail No witnesses remain**

**1979 Soderberg L3218, P53 Found 1/2" rered in monument box**

**PLATS**

**1941 Supervisor's Plat No. 6 of Sherman's Small Farms Subdivision L20, P44**

**FIELD EVIDENCE:**

**I found a 1/2" rered in an monument box near the center of Masonic Avenue (concrete) and the East Right of Way line of Little Mack Avenue. Several irons to the West, East and South verify this position.**

**RECOMMENDATION:**

**I recommend accepting the found 1/2" rered in the monument box as the best position for this corner.**

**DISTANCES:**

**G-02 TO G-01**

**GLO 40 chains or 2640 feet**

**Measure 2690.75 feet**

**G-02 to G-03**

**GLO 40 chains or 2640'**

**Measure 2688.96 Feet**

**I-02 CLINTON TOWNSHIP**

**WITNESSES:**

**S65°W 113.55'**

**N70°W 112.22'**

**North 42.41'**

**S10°W 56.87'**

**Set PK nail with MC Remon tag in SE face Utility Pole**

**Centerline East Bolt on Metal Light Pole**

**Southwest corner Brick Pillar**

**Set PK nail MC Remon tag in West face Utility pole**